

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

U.S. PATENTS FOR NASA INVENTIONS

Available for Licensing in the United States

* Many Have Commercial Use *

FACILITY FORM 602

| | |
|---|-------------------------|
| <u>N71-12424</u> (ACCESSION NUMBER) | <u>Q3</u> (THRU) |
| <u>13</u> (PAGES) | <u>34</u> (CODE) |
| <u>TMX-66495</u> (NASA CR OR TMX OR AD NUMBER) | <u>34</u> (CATEGORY) |



National Aeronautics and Space Administration



34

PRECEDING PAGE BLANK NOT FILMED

NASA DOMESTIC PATENT LICENSING PROGRAM

Several thousand inventions result each year from the aeronautical and space research supported by the National Aeronautics and Space Administration. These inventions cover practically all fields of technology and include many that have useful and valuable commercial application.

The inventions having important use in Government programs or significant commercial potential are patented by NASA. In order to encourage the widest possible commercial use of these inventions, NASA makes its patents and applications for patent available for commercial licensing in accordance with the NASA Patent Licensing Regulations, Title 14 Code of Federal Regulations Section 1245.200 et seq.

NASA will grant nonexclusive, royalty-free licenses for inventions covered by patents and applications for patent for the term of the patent unless subsequently revoked or terminated by either party pursuant to agreed upon conditions. If commercial use of an invention has not occurred by the end of the second year after the issue date of the patent, an exclusive, royalty-free license may be granted by NASA to a qualified applicant thereby adding the incentive of exclusivity to encourage the commercial development of the invention.

ADDRESS

Inquiries and all applications for licenses should be addressed to:

Assistant General Counsel for Patent Matters
National Aeronautics and Space Administration
Washington, D.C. 20546

APPLICATION FOR LICENSE

An application for a patent license shall include:

1. Identification of invention for which license is desired:
 - Title of invention
 - U.S. Patent No. or Application No. (if known)
 - NASA Tech Brief No. (if applicable)
 - Other identification of invention (if any)
2. Name and address of company or organization applying for license
3. Name and address of representative or applicant to whom correspondence should be sent
4. Nature and type of applicant's business
5. Number of employees
6. Identification of source of information about the availability of a license on this invention
7. Purpose for which license is desired.

An application for exclusive license shall also include:

8. Applicant's status, if any, in any one or more of the following categories: (a) small business firms; (b) location in a surplus labor area; (c) location in a low income urban area; and (d) location in an area designated by the Government as economically depressed.

9. A description of applicant's capability to undertake the industrial marketing and development required to achieve the practical application of the invention.
10. The time and expenditure which the applicant estimates to be required to develop the invention to the point of practical application and the applicant's intention to invest that sum of money in development of the invention if the license is granted.
11. Whether the applicant would be willing to accept an exclusive license in a limited field of use or for any geographic portion less than the entirety of the United States of America, its territories and possessions, and if so, define the geographic portion or limited field.
12. Any other facts which the applicant believes to show it to be in the interests of the United States of America for the Administration to grant an exclusive license rather than a nonexclusive license and that such an exclusive license should be granted to the applicant.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

U.S. PATENTS AVAILABLE FOR LICENSING

Listed below are the U.S. patents available for royalty-free licensing from the National Aeronautics and Space Administration. Copies of the patents may be purchased directly from the U.S. Patent Office, Washington, D.C., for fifty cents a copy. Any NASA patent more than two years old and not in commercial use may be available for exclusive licensing. The patents marked with an asterisk (*) are believed to have good commercial potential use without much further development. Those marked with a double asterisk (**) have good potential, but may require further development for commercial use.

| Patent No. | Date | Title | Patent No. | Date | Title |
|------------|----------|---|-------------|----------|---|
| 2,837,706 | 6-3-58 | Line Following Servosystem | 3,049,876 | 8-21-62 | Annular Rocket Motor and Nozzle Configuration |
| 2,898,889 | 8-11-59 | Mechanically-Limited Electrically Operated Hydraulic Valve System for Aircraft Controls | 3,053,484 | 9-11-62 | Variable Sweep Wing Configuration |
| 2,903,307 | 9-8-59 | Two Component Bearing | 3,057,597 | 10-9-62 | Modification and Improvements to Cooled Blades |
| 2,926,123 | 2-23-60 | Temperature Reducing Coating for Metals Subject to Flame Exposure | 3,059,220 | 10-16-62 | Apparatus for Coupling a Plurality of Ungrounded Circuits to a Grounded Circuit |
| 2,934,331 | 4-26-60 | Apparatus for Making a Metal Slurry Product | 3,063,291 | 11-13-62 | High Vacuum Condenser Tank for Ion Rocket Engines |
| 2,940,259 | 6-14-60 | Rocket Propellant Injector | 3,064,928 | 11-20-62 | Variable Sweep Wing Aircraft |
| 2,944,316 | 7-12-60 | Process of Casting Heavy Slips | 3,067,573 | 12-11-62 | Telescoping-Spike Supersonic Inlet for Aircraft Engines |
| 2,945,667 | 7-19-60 | Flexible Seal for Valves | 3,068,658 | 12-18-62 | Venting Vapor Apparatus |
| 2,956,772 | 10-18-60 | Liquid-Spray Cooling Method | 3,069,123 | 12-18-62 | Instrument Support with Precise Lateral Adjustment |
| 2,971,837 | 2-14-61 | High Temperature Nickel-Base Alloy | 3,070,330 | 12-25-62 | Attitude and Propellant Flow Control System and Method |
| 2,971,838 | 2-14-61 | High Temperature Nickel-Base Alloy | 3,070,349 | 12-25-62 | Multistage Multiple-Reentry Turbine |
| 2,974,925 | 3-14-61 | External Liquid-Spray Cooling of Turbine Blades | 3,070,407 | 12-25-62 | Air Bearing |
| 2,984,735 | 5-14-61 | Runway Light | 3,072,574 | 1-8-63 | Gas Lubricant Compositions |
| 2,991,671 | 7-11-61 | Wire Grid Forming Apparatus | 3,076,065 | 1-29-63 | High-Speed Low-Level Electrical Stepping Switch |
| 2,991,961 | 7-11-61 | Jet Aircraft Configuration | 3,077,599 | 2-12-63 | Collapsible Loop Antenna for Space Vehicle |
| 2,996,212 | 8-15-61 | Self Supporting Space Vehicle | 3,079,113 | 2-26-63 | Vehicle Parachute and Equipment Jettison System |
| 2,997,274 | 8-22-61 | Turbo-Machine Blade Vibration Damper | 3,080,711 | 3-12-63 | Penshape Exhaust Nozzle for Supersonic Engine |
| 3,001,363 | 9-26-61 | Spherical Solid-Propellant Rocket Motor | 3,083,611 | 4-2-63 | Multi-Lobar SCAN Horizon Sensor |
| 3,001,395 | 9-26-61 | Air Frame Drag Balance | 3,084,421 | 4-9-63 | Reinforced Metallic Composites |
| 3,001,739 | 9-26-61 | Aerial Capsule Emergency Separation Device | 3,085,165 | 4-9-63 | Ultra-Long Monostable Multivibrator Employing Bistable Semiconductor Switch to Allow Charging or Timing Circuit |
| 3,004,735 | 10-17-61 | Particle Detection Apparatus | 3,087,692 | 4-30-63 | Variable-Span Aircraft |
| 3,005,081 | 10-17-61 | High Intensity Heat and Light Unit | 3,088,441 | 5-7-63 | Valve Actuator |
| 3,005,339 | 10-24-61 | Wind Tunnel Airstream Oscillating Apparatus | **3,090,212 | 5-21-63 | Sandwich Panel Construction |
| 3,008,229 | 11-14-61 | Process for Applying a Protective Coating for Salt Bath Brazing | 3,090,580 | 5-21-63 | Space and Atmospheric Reentry Vehicle |
| 3,010,372 | 11-28-61 | Folding Apparatus | 3,093,000 | 6-11-63 | Check Valve Assembly for a Probe |
| 3,011,760 | 12-5-61 | Transportation Cooled Turbine Blade Manufactured from Wires | 3,093,346 | 6-11-63 | Space Capsule |
| 3,012,400 | 12-21-61 | Nozzle | 3,098,630 | 7-23-63 | Annular Supersonic Decelerator or Drogue |
| 3,012,407 | 12-21-61 | Insulating Structure | **3,100,294 | 8-6-63 | Time-Division Multiplexer |
| 3,016,693 | 1-16-62 | Electro-Thermal Rocket | 3,100,990 | 8-20-63 | Two-Plane Balance |
| 3,016,863 | 1-16-62 | Hydrofoil | 3,102,948 | 9-3-63 | Electric Arc Welding |
| 3,022,672 | 2-27-62 | Differential Pressure Cell | 3,104,079 | 9-17-63 | Variable-Geometry Winged Reentry Vehicle |
| 3,024,659 | 3-13-62 | Magnetically Centered Liquid Column Float | **3,104,082 | 9-17-63 | Variable Sweep Aircraft Wing |
| 3,028,122 | 4-3-62 | Landing Arrangement for Aerial Vehicles | 3,105,515 | 10-1-63 | Pressure Regulating System |
| 3,028,126 | 4-3-62 | Three Axis Controller | **3,106,603 | 10-8-63 | High Voltage Cable |
| 3,028,128 | 4-3-62 | Reentry Vehicle Leading Edge | 3,108,171 | 10-22-63 | Radiant Heater Having Formed Filaments |
| 3,038,077 | 6-5-62 | Infrared Scanner | | | |
| 3,038,175 | 6-12-62 | Survival Couch | | | |
| 3,041,587 | 6-26-62 | Angular Measurement System | | | |
| 3,041,924 | 7-3-62 | Motion Picture Camera for Optical Pyrometry | | | |
| 3,045,424 | 7-24-62 | Method for Continuous Variation of Propellant Flow and Thrust in Propulsive Devices | | | |

| Patent No. | Date | Title |
|-------------|----------|--|
| 3,110,318 | 11-12-63 | Slosh Suppressing Device and Method |
| 3,112,672 | 12-3-63 | Umbilical Separator for Rockets |
| 3,115,630 | 12-24-63 | Reflector Space Satellite |
| 3,118,100 | 1-14-64 | Electric Battery and Method of Operating the Same |
| 3,119,232 | 1-28-64 | Rocket Engine |
| 3,120,101 | 2-4-64 | Channel Type Shell Construction for Rocket Engine and the Like |
| 3,120,361 | 2-4-64 | Landing Arrangement for Aerospace Vehicle |
| 3,120,738 | 2-11-64 | Ignition System for Monopropellant Combustion Devices |
| 3,121,309 | 2-18-64 | Spherically Shaped Rocket Motor |
| 3,122,000 | 2-25-64 | Apparatus for Transferring Cryogenic Liquids |
| 3,122,098 | 2-25-64 | Apparatus and Method for Control of a Solid Fueled Rocket Vehicle |
| 3,122,885 | 3-3-64 | Injector for Bipropellant Rocket Engines |
| 3,123,248 | 3-3-64 | Expulsion Bladder Equipped Storage Tank Structure |
| **3,127,157 | 3-31-64 | Multiple Belleville Spring Assembly |
| 3,128,389 | 4-7-64 | Variable Frequency Magnetic Multivibrator |
| 3,128,845 | 4-14-64 | Despin Weight Release |
| 3,130,940 | 4-28-64 | Heat Shield |
| 3,132,342 | 5-5-64 | Antenna System Using Parasitic Elements and Two Driven Elements at 90° Angle Fed 180° Out of Phase |
| 3,132,476 | 5-12-64 | Thrust Vector Control Apparatus |
| 3,132,479 | 5-12-64 | Universal Restrainer and Joint |
| **3,132,903 | 5-12-64 | Slit Regulated Gas Journal Bearing |
| 3,135,089 | 6-2-64 | Decomposition Unit |
| 3,135,090 | 6-2-64 | Rocket Motor System |
| 3,136,123 | 6-9-64 | Rocket Engine Injector |
| 3,138,837 | 6-30-64 | Method of Making Fiber Reinforced Metallic Composites |
| 3,139,725 | 7-7-64 | Steerable Solid Propellant Rocket Motor |
| **3,140,728 | 7-14-64 | High Pressure Four-Way Valve |
| 3,141,340 | 7-21-64 | Gravity Device |
| 3,141,769 | 7-21-64 | Method of Producing Porous Tungsten Ionizers for Ion Rocket Engines |
| 3,141,932 | 7-21-64 | Switching Mechanism with Energy Storage Means |
| **3,143,321 | 8-4-64 | Frangible Tube Energy Dissipation |
| 3,143,651 | 8-4-64 | X-Ray Reflection Collimator Adapted For Focus X-Radiation Directly On A Detector |
| 3,144,219 | 8-11-64 | Manned Space Station |
| 3,144,999 | 8-18-64 | Propellant Blade Loading Control |
| 3,145,874 | 8-18-64 | Means For Controlling Repture Of Shock Tube Diaphragms |
| 3,147,422 | 9-1-64 | Electronic Motor Control System |
| 3,149,897 | 9-22-64 | Printed Cable Connector |
| 3,150,329 | 9-22-64 | Variable Frequency Magnetic Coupled Multivibrator |
| **3,150,387 | 9-29-64 | Foam Generator |
| *3,152,344 | 10-13-64 | Life Preserver |
| 3,155,992 | 11-10-64 | Life Raft |
| 3,156,090 | 11-10-64 | Ion Rocket |
| 3,157,529 | 11-17-64 | Bonded Solid Lubricant Coating |
| 3,158,172 | 11-24-64 | High-Temperature, High-Pressure Spherical Segment Valve |
| 3,158,336 | 11-24-64 | Assembly for Recovering a Capsule |
| **3,158,764 | 11-24-64 | Two-Fluid Magneto-hydrodynamic System and Method for Thermal-Electric Power Conversion |
| 3,159,967 | 12-8-64 | Variable Thrust Ion Engine Utilizing Thermally Decomposable Solid Fuel |
| **3,160,825 | 12-8-64 | Temperature Compensating Means for Cavity Resonator of Amplifier |

| Patent No. | Date | Title |
|-------------|----------|---|
| **3,160,950 | 12-15-64 | Method and Apparatus for Shock Protection |
| 3,162,012 | 12-22-64 | Formed Metal Ribbon Wrap |
| **3,163,935 | 1-5-65 | Mechanical Coordinate Converter |
| 3,164,222 | 1-5-65 | Non-Reusable Kinetic Energy Absorber |
| 3,164,369 | 1-5-65 | Multistage Multiple-Reentry Turbine |
| 3,165,356 | 1-12-65 | Shock Absorbing Support and Restraint Means |
| 3,166,834 | 1-26-65 | Catalyst Bed Removing Tool |
| 3,167,426 | 1-26-65 | Nickel-Base Alloy |
| 3,168,827 | 2-9-65 | Airplane Take-off Performance Indicator |
| *3,169,001 | 2-9-65 | Aircraft Wheel Spray Drag Alleviator |
| **3,169,613 | 2-16-65 | Elastically Universal Joint |
| **3,169,725 | 2-16-65 | Erectable Modular Space Station |
| 3,170,286 | 2-23-65 | Injector Valve Device |
| 3,170,290 | 2-23-65 | Liquid Rocket System |
| 3,170,295 | 2-23-65 | Propellant Tank Pressurization System |
| 3,170,324 | 2-23-65 | Aerodynamic Measuring Device |
| **3,170,471 | 2-23-65 | Inflatable Honeycomb |
| 3,170,486 | 2-23-65 | Two-Component Valve Assembly |
| 3,170,605 | 2-23-65 | Ejection Valve |
| 3,170,657 | 2-23-65 | Landing Arrangement for Aerial Vehicle |
| 3,170,660 | 2-23-65 | Parachute Glider |
| 3,170,773 | 2-23-65 | Reinforced Metallic Composites |
| 3,171,060 | 2-23-65 | Plasma Accelerator |
| 3,171,081 | 2-23-65 | Ionization Vacuum Gauge |
| 3,172,097 | 3-2-65 | Binary to Binary-Coded-Decimal Converter |
| 3,173,246 | 3-16-65 | Colloid Propulsion Method and Apparatus |
| 3,173,251 | 3-16-65 | Apparatus for Igniting Solid Propellants |
| 3,174,278 | 3-23-65 | Continuously Operating Induction Plasma |
| 3,174,279 | 3-23-65 | Rocket Thrust Chamber |
| 3,174,827 | 3-23-65 | Production of High Purity Silicon Carbide |
| 3,175,789 | 3-30-65 | Landing Pad Assembly for Aerospace Vehicles |
| 3,176,222 | 3-30-65 | Apparatus Having Coaxial Capacitor Structure for Measuring Fluid Density |
| 3,176,499 | 4-6-65 | High Temperature Testing Apparatus |
| 3,176,933 | 4-6-65 | Thermal Control of Space Vehicles |
| *3,177,933 | 4-13-65 | Thermal Switch |
| 3,178,883 | 4-20-65 | Attitude Control for Spacecraft |
| 3,180,264 | 4-27-65 | Coupling for Linear Shaped Charge |
| 3,180,587 | 4-27-65 | Attitude Orientation of Spin-Stabilized Space Vehicles |
| 3,181,821 | 5-4-65 | Spacecraft Soft Landing System |
| 3,182,496 | 5-11-65 | Electric Arc Driven Wind Tunnel |
| 3,183,506 | 5-11-65 | Radar Ranging Receiver |
| 3,185,023 | 5-25-65 | Optical Inspection Apparatus |
| 3,187,583 | 6-8-65 | Space Simulator |
| 3,188,472 | 6-8-65 | Method and Apparatus for Determining Satellite Orientation Utilizing Spatial Energy Sources |
| 3,188,844 | 6-15-65 | Electrical Discharge Apparatus for Forming |
| 3,189,299 | 6-15-65 | Dynamic Precession Damper for Spin Stabilized Vehicles |
| **3,189,535 | 6-15-65 | Means and Method of Depositing Thin Films on Substrates |
| 3,189,726 | 6-15-65 | High Temperature Heat Source |
| 3,189,794 | 6-15-65 | Relay Binary Circuit |
| 3,189,864 | 6-15-65 | Electrical Connector for Flat Cables |
| 3,191,316 | 6-29-65 | Lunar Landing Flight Research Vehicle |
| 3,191,379 | 6-29-65 | Propellant Grain for Rocket Motors |

| Pat. No. | Date | Title |
|-------------|----------|--|
| 3,191,907 | 6-29-65 | Conical Valve Plug |
| 3,192,730 | 7-6-65 | Helium Refining by Superfluidity |
| 3,193,883 | 7-13-65 | Mandrel for Shaping Solid Propellant Rocket Fuel into a Motor Casing |
| 3,194,060 | 7-13-65 | Seismic Displacement Transducer |
| 3,194,525 | 7-13-65 | Supporting and Protecting Device |
| 3,194,951 | 7-13-65 | Logarithmic Converter |
| 3,196,261 | 7-20-65 | Full Binary Adder |
| 3,196,362 | 7-20-65 | Temperature Compensated Solid State Differential |
| 3,196,557 | 7-27-65 | Centrifuge Mounted Motion Simulator |
| 3,196,558 | 7-27-65 | Means for Visually Indicating Flight Paths of Vehicles Between the Earth |
| 3,196,598 | 7-27-65 | Inlet Deflector for Jet Engines |
| 3,196,675 | 7-27-65 | Optical Torquemeter |
| 3,196,690 | 7-27-65 | Impact Simulator |
| 3,197,616 | 7-27-65 | Temperature Regulation Circuit |
| 3,198,955 | 8-3-65 | Binary Magnetic Memory Device |
| 3,199,340 | 8-10-65 | Accelerometer with F.M. Output |
| 3,199,343 | 8-10-65 | Electric Propulsion Engine Test Chamber |
| 3,199,931 | 8-10-65 | Externally Pressurized Fluid Bearing |
| 3,200,706 | 8-17-65 | Gas Actuated Bolt Disconnect |
| 3,201,560 | 8-17-65 | Electric-Arc Heater |
| 3,201,635 | 8-17-65 | Method and Apparatus for Producing a Plasma |
| 3,201,980 | 8-24-65 | Thrust Dynamometer |
| 3,202,381 | 8-24-65 | Recoverable Rocket Vehicle |
| 3,202,398 | 8-24-65 | Locking Device for Turbine Rotor Blades |
| 3,202,844 | 8-24-65 | Energy Conversion Apparatus |
| 3,202,915 | 8-24-65 | Particle Beam Measurement Apparatus Using Beam Kinetic Energy to Change the Heat Sensitive Resistance of the Detection Probe |
| **3,202,998 | 8-24-65 | Flexible Foam Erectable Space Structure |
| 3,204,447 | 9-7-65 | Enthalpy and Stagnation Temperature Determination of a High Temperature Laminar Flow Gas Stream |
| 3,204,889 | 9-7-65 | Space Vehicle Electrical System |
| 3,205,361 | 9-7-65 | Light Sensitive Digital Aspect Sensor |
| 3,205,362 | 9-7-65 | Photosensitive Device to Detect Bearing Deviation |
| 3,205,381 | 9-7-65 | Ionospheric Battery |
| 3,206,141 | 9-14-65 | Space Vehicle Attitude Control |
| 3,208,215 | 9-28-65 | Gimbaled, Partially Submerged Rocket Nozzle |
| 3,208,272 | 9-28-65 | Surface Roughness Detector |
| 3,208,694 | 9-28-65 | Nose Gear Steering System for Vehicle with Main Skid |
| 3,208,707 | 9-28-65 | Pivotal Shock Absorbing Pad Assembly |
| 3,209,360 | 9-28-65 | Antenna Beam-Shaping Apparatus |
| 3,209,361 | 9-28-65 | Cassegrainian Antenna Subreflector Flange for Suppressing Ground Noise |
| 3,210,927 | 10-12-65 | Electro-Thermal Rockets Having Improved Heat Exchangers |
| 3,211,169 | 10-12-65 | Shrink-fit Gas Valve |
| 3,211,414 | 10-12-65 | Thermally Operated Valve |
| 3,212,096 | 10-12-65 | Parabolic Reflector Horn Feed With Spillover Correction |
| 3,212,259 | 10-15-65 | Tertiary Flow Injection Thrust Vectoring System |
| 3,212,325 | 10-12-65 | Force Measuring Instrument |
| 3,212,564 | 10-19-65 | Heat Conductive Resiliently Compressible Structure for Space Electronic Package Modules |
| 3,215,572 | 11-02-65 | Low Viscosity Magnetic Fluid Obtained by the Colloidal Suspension of Magnetic Particles |
| *3,215,842 | 11-02-65 | Optical Communication System |
| 3,216,007 | 11-02-65 | Analog-to-Digital Conversion System |
| **3,217,624 | 11-16-65 | Electrically-operated Rotary Shutter |
| 3,218,479 | 11-16-65 | Phase Detector Assembly |

| Parent No. | Date | Title |
|-------------|----------|---|
| 3,218,547 | 11-16-65 | Flux Sensing Device Using a Tubular Core with Toroidal Gating Coil and Solenoidal Output Coil |
| 3,218,850 | 11-23-65 | Thermo-protective Device for Balances |
| 3,219,250 | 11-23-65 | Flexible Back-up Bar |
| 3,219,365 | 11-23-65 | Spherical Shell |
| 3,219,828 | 11-23-65 | Vibrating Reticle Star Tracker |
| 3,220,004 | 11-23-65 | Passive Communication Satellite |
| 3,221,547 | 12-7-65 | Apparatus for Absorbing and Measuring Power |
| **3,221,549 | 12-7-65 | Aircraft Instrument |
| *3,223,374 | 12-14-65 | Miniature Vibration Isolator |
| 3,224,001 | 12-14-65 | Inflatable Radar Reflector Unit |
| 3,224,173 | 12-21-65 | Liquid-gas Separator System |
| 3,224,263 | 12-21-65 | Null-type Vacuum Microbalance |
| 3,224,336 | 12-21-65 | Missile Launch Release System |
| 3,228,492 | 1-11-66 | Double-Acting Shock Absorber |
| 3,228,558 | 1-11-66 | Measuring Device |
| 3,229,059 | 1-11-66 | Electro-Optical Alignment Control System |
| 3,229,102 | 1-11-66 | Radiation Direction Detector Including Means for Compensating for Photocell Aging |
| 3,229,139 | 1-11-66 | High Temperature Spark Plug |
| 3,229,155 | 1-11-66 | Electric Arc Device for Heating Gases |
| 3,229,463 | 1-18-66 | Trajectory-correction Propulsion System |
| 3,229,568 | 1-18-66 | Concave Grating Spectrometer |
| 3,229,636 | 1-18-66 | Missile Stage Separation Indicator and Stage Initiator |
| 3,229,682 | 1-18-66 | Device for Directionally Controlling Electromagnetic Radiation |
| 3,229,689 | 1-18-66 | Resuscitation Apparatus |
| 3,229,884 | 1-18-66 | Segmented Back-up Bar |
| 3,229,930 | 1-18-66 | Stretch Yo-Yo De-spin Mechanism |
| **3,230,053 | 1-18-66 | Apparatus for Producing High Purity Silicon Carbide Crystals |
| 3,230,377 | 1-18-66 | Self-stabilized Theodolite for Manual Tracking Using Photosensitive Stabilizing Means |
| 3,236,066 | 2-22-66 | Energy Absorption Device |
| 3,237,253 | 3-1-66 | Method of Making Screen by Casting |
| 3,238,345 | 3-1-66 | Hypersonic Test Facility |
| 3,238,413 | 3-1-66 | Magnetically Controlled Plasma Accelerator |
| 3,238,715 | 3-8-66 | Electrostatic Ion Engine Having a Permanent Magnetic Circuit |
| 3,238,730 | 3-8-66 | Anti-backlash Circuit for Hydraulic Drive System |
| 3,238,774 | 3-8-66 | Pressurized Cell Micrometeroid Detector |
| *3,238,777 | 3-8-66 | Differential Temperature Transducer |
| 3,239,660 | 3-8-66 | Illumination System Including a Virtual Light Source |
| 3,242,716 | 3-29-66 | Apparatus for Measuring Thermal Conductivity |
| 3,243,154 | 3-29-66 | Vibration Damping System |
| 3,243,791 | 3-29-66 | Bi-carrier Demodulator with Modulation |
| 3,249,012 | 5-3-66 | Umbilical Disconnect |
| **3,249,013 | 5-3-66 | Remote Controlled Tubular Disconnect |
| 3,251,053 | 5-10-66 | Analog to Digital Converter |
| 3,252,100 | 5-17-66 | Pulse Generating Circuit |
| 3,254,395 | 6-7-66 | Method for Making a Rocket Motor Casing |
| 3,254,487 | 6-7-66 | Rocket Motor Casing |
| 3,257,780 | 6-28-66 | Zero Gravity Separator |
| 3,258,582 | 6-28-66 | Energy Management System for Glider Type Vehicle |
| 3,258,687 | 6-28-66 | Wide Range Linear Fluxgate Magnetometer |
| 3,258,831 | 7-5-66 | Method of Making a Molded Connector |

| Patent No. | Date | Title |
|-------------|---------|---|
| 3,258,912 | 7-5-66 | Method of Igniting Solid Propellants |
| 3,258,918 | 7-5-66 | Fluid Dispensing Apparatus and Method |
| **3,260,055 | 7-12-66 | Automatic Thermal Switch |
| 3,260,204 | 7-12-66 | Velocity Package |
| 3,260,326 | 7-12-66 | Wind-tunnel Microphone Structure |
| 3,261,210 | 7-19-66 | Superconductive Accelerometer |
| 3,262,186 | 7-26-66 | Method of Improving the Reliability of a Rolling Element System |
| 3,262,262 | 7-26-66 | Electrostatic Ion Rocket Engine |
| 3,262,351 | 7-26-66 | Separation Nut |
| 3,262,365 | 7-26-66 | Space Capsule Ejection Assembly |
| 3,262,395 | 7-26-66 | Hydraulic Transformer |
| 3,262,518 | 7-26-66 | Emergency Escape System |
| 3,262,655 | 7-26-66 | Alleviation of Divergence During Rocket Launch |
| 3,263,016 | 7-26-66 | Black-body Furnace |
| 3,263,171 | 7-26-66 | Micro Current Measuring Device Using Plural Logarithmic Response Heated Filamentary Type Diodes |
| 3,263,610 | 8-2-66 | Quick-Release Connector |
| **3,264,135 | 8-2-66 | Method of Coating Carbonaceous Base To Prevent Oxidation Destruction and Coated Base |
| 3,270,441 | 9-6-66 | Reduced Gravity Simulator |
| 3,270,499 | 9-6-66 | Injector Assembly for Liquid Fueled Rocket Engines |
| 3,270,501 | 9-6-66 | Aerodynamic Spike Nozzle |
| 3,270,503 | 9-6-66 | Ablation Structures |
| 3,270,504 | 9-6-66 | Automatically Deploying Nozzle Exit Cone Extension |
| 3,270,505 | 9-6-66 | Control System for Rocket Vehicles |
| **3,270,512 | 9-6-66 | Intermittent Type Silica gel Absorption Refrigerator |
| 3,270,565 | 9-6-66 | Omnidirectional Acceleration Device |
| 3,270,756 | 9-6-66 | Fluid Flow Control Valve |
| 3,270,802 | 9-6-66 | Method and Apparatus for Varying Thermal Conductivity |
| 3,270,835 | 9-6-66 | Device for Suppressing Sound and Heat Produced by High-velocity Exhaust Jets |
| 3,270,908 | 9-6-66 | Space Capsule |
| 3,270,985 | 9-6-66 | Reactance Control System |
| 3,270,986 | 9-6-66 | Hand-held Self-maneuvering Unit |
| 3,270,988 | 9-6-66 | Minimum Induced Drag Airfoil Body |
| **3,270,989 | 9-6-66 | Variable Sweep Aircraft |
| 3,270,990 | 9-6-66 | Absorptive Splitter for Closely Spaced Supersonic Engine Air Inlets |
| 3,271,140 | 9-6-66 | High Temperature Cobalt-Base Alloy |
| **3,271,181 | 9-6-66 | Method of Coating Carbonaceous Base To Prevent Oxidation Destruction and Coated Base |
| 3,271,532 | 9-6-66 | Three-axis Finger Tip Controller for Switches |
| 3,271,558 | 9-6-66 | Spectral Method for Monitoring Atmospheric Contamination of Inert-gas Welding Shields |
| 3,271,594 | 9-6-66 | Transient Augmentation Circuit for Pulse Amplifiers |
| **3,271,620 | 9-6-66 | Starting Circuit for Vapor Lamps and the Like |
| 3,271,637 | 9-6-66 | Gas Solar Detector Using Manganese as a Doping Agent |
| 3,271,649 | 9-6-66 | Regenerative Braking System |
| 3,273,094 | 9-13-66 | Superconducting Magnet |
| 3,273,355 | 9-20-66 | Heat Protective Apparatus |
| 3,273,381 | 9-20-66 | Means and Method of Measuring Viscoelastic Strain |
| 3,273,388 | 9-20-66 | Apparatus for Measuring Electric Field Strength on the Surface of a Model Vehicle |
| 3,273,392 | 9-20-66 | Hot Wire Liquid Level Detector for Cryogenic Fluids |
| 3,273,399 | 9-20-66 | Traversing Probe |

| Patent No. | Date | Title |
|-------------|----------|---|
| 3,274,304 | 9-20-66 | Method of Making Impurity-Type Semiconductor Electrical Contacts |
| *3,276,251 | 10-4-66 | Test Unit Pre-Flight Suspension System |
| 3,276,376 | 10-4-66 | Thrust and Direction Control Apparatus |
| 3,276,602 | 10-4-66 | Cable Arrangement for Rigid Tethering Separator |
| 3,276,679 | 10-4-66 | Flight Craft |
| 3,276,722 | 10-4-66 | Inflation System for Balloon Type Satellites |
| 3,276,726 | 10-4-66 | High Temperature Cobalt-Base Alloy |
| 3,276,865 | 10-4-66 | Nickel-Base Alloy Containing Mo-W-Al-Cr-Ta-Zr-C-Nb-B |
| 3,276,866 | 10-4-66 | Low Friction Magnetic Recording Tape |
| 3,276,946 | 10-4-66 | High-Efficiency Multivibrator |
| 3,277,314 | 10-4-66 | Insertion Loss Measuring Apparatus Having Transformer Means Connected Across a Pair of Bolometers |
| 3,277,366 | 10-4-66 | Serrodyne Frequency Converter Re-entrant Amplifier System |
| 3,277,373 | 10-4-66 | Reentry Communication by Material Addition |
| 3,277,375 | 10-4-66 | Condition and Condition Duration Indicator |
| 3,277,458 | 10-4-66 | Method and Means for Damping Nutation in a Satellite |
| 3,277,486 | 10-4-66 | Method and Construction for Protecting Heat Sensitive Bodies From Thermal Radiation and Convective Heat |
| 3,279,193 | 10-18-66 | Training Vehicle for Controlling Attitude |
| 3,281,963 | 11-01-66 | Rotating Space Station Simulator |
| 3,281,964 | 11-01-66 | Controlled Visibility Device for an Aircraft |
| **3,281,965 | 11-01-66 | Molecular Beam Velocity Selector |
| 3,282,035 | 11-01-66 | Instrument for Measuring Torsional Creep and Recovery |
| 3,282,091 | 11-01-66 | Stabilization of Gravity Oriented Satellites |
| 3,282,532 | 11-01-66 | Attitude Control System for Sounding Rockets |
| 3,282,541 | 11-01-66 | Non-magnetic Battery Case |
| 3,282,739 | 11-01-66 | Sealed Battery Gas Manifold Construction |
| **3,282,740 | 11-01-66 | Multiple Circuit Switch Apparatus With Improved Pivot Actuator Structure |
| 3,283,088 | 11-01-66 | AC Logic Flip-Flop Circuits |
| 3,283,175 | 11-01-66 | Apparatus for Field Strength Measurement of a Space Vehicle |
| 3,283,241 | 11-01-66 | Pressure suit tie-down mechanism |
| 3,286,274 | 11-22-66 | Omni-Directional Anisotropic Molecular Trap |
| 3,286,531 | 11-22-66 | Multi-mission module |
| 3,286,629 | 11-22-66 | Spacecraft separation system for spinning vehicles and/or payloads |
| 3,286,630 | 11-22-66 | Booster tank system |
| 3,286,882 | 11-22-66 | Roll attitude star sensor system |
| 3,286,953 | 11-22-66 | Flexible wing deployment device |
| 3,286,957 | 11-22-66 | Indexed Keyed Connection |
| 3,287,031 | 11-22-66 | Prevention of pressure build-up in electrochemical cells |
| 3,287,174 | 11-22-66 | Digital television camera control system |
| 3,287,496 | 11-22-66 | Apparatus for increasing ion engine beam density |
| 3,287,582 | 11-22-66 | Pulse Counting circuit which simultaneously indicates the occurrence of the Nth pulse |
| 3,287,640 | 11-22-66 | Solid State chemical source for ammonia beam maser |
| **3,287,660 | 11-22-66 | Phase-locked loop with a sideband rejecting properties |
| 3,287,725 | 11-22-66 | Method & Apparatus for determining Electromagnetic characteristics of Large Surface Area Passive Reflectors |
| 3,289,205 | 11-29-66 | |

| Patent No. | Date | Title |
|-------------|----------|--|
| 3,295,360 | 01-03-67 | Dynamic sensor |
| *3,295,366 | 01-03-67 | Support apparatus for dynamic testing |
| 3,295,377 | 01-03-67 | Angular accelerometer |
| 3,295,386 | 01-03-67 | Three axis controller |
| 3,295,512 | 01-03-67 | Foldable solar concentrator |
| 3,295,545 | 01-03-67 | Liquid storage tank venting device for zero gravity environment |
| 3,295,556 | 01-03-67 | Foldable conduit |
| **3,295,684 | 01-03-67 | High pressure filter |
| 3,295,699 | 01-03-67 | Folding boom assembly |
| 3,295,782 | 01-03-67 | Endless tape cartridge |
| 3,295,790 | 01-03-67 | Recoverable single stage spacecraft booster |
| 3,295,791 | 01-03-67 | Storage container mounting for space vehicles |
| 3,295,798 | 01-03-67 | Landing gear |
| **3,295,808 | 01-03-67 | Parallel motion suspension device |
| 3,296,060 | 01-03-67 | Unrefined-ceramic flame resistant insulation and method of making the same |
| 3,296,526 | 01-03-67 | Micrometeroid velocity measuring device |
| 3,296,531 | 01-03-67 | Electrostatic plasma modulator for space vehicle re-entry communication |
| 3,298,175 | 01-17-67 | Method and device for cooling |
| 3,298,182 | 01-17-67 | Ignition means for monopropellant |
| 3,298,221 | 01-17-67 | Densitometer |
| 3,298,285 | 01-17-67 | Reinforcing means for diaphragms |
| 3,298,362 | 01-17-67 | Instrument for use in performing a controller Valsalva Maneuver |
| 3,298,582 | 01-17-67 | Camera film feed having a detent means |
| *3,299,364 | 01-17-67 | Folded traveling wave maser structure |
| 3,299,431 | 01-17-67 | Unfurlable structure including coiled strips thrust launched upon tension release |
| 3,299,913 | 01-24-67 | Adjustable Tension Wire Guide |
| 3,300,162 | 01-24-67 | Radial module space station |
| 3,300,717 | 01-24-67 | Method & Apparatus for measuring potentials in plasmas |
| 3,300,721 | 01-24-67 | Means for communication through a layer of ionized gases |
| 3,300,847 | 01-31-67 | Portable alignment tool |
| 3,300,949 | 01-31-67 | Liquid-gas separator for zero gravity environment |
| 3,300,981 | 01-31-67 | Zero gravity starting means for liquid propellant motors |
| 3,301,046 | 01-37-67 | Method of obtaining permanent record of surface flow phenomena |
| 3,301,315 | 01-31-67 | Thermal conductive connection and method of making same |
| 3,301,507 | 01-31-67 | Hypersonic Re-entry Vehicle |
| 3,301,511 | 01-31-67 | Wing Deployment Method and Apparatus |
| 3,301,578 | 01-31-67 | Cryogenic connector for vacuum use |
| 3,302,023 | 01-31-67 | Apparatus for producing three dimensional recordings of fluorescence spectra |
| 3,302,040 | 01-31-67 | Linear sawtooth voltage-wave generator employing transistor timing circuit having capacitor-zener diode combination feedback |
| 3,302,569 | 02-07-67 | Quick release separation mechanism |
| 3,302,633 | 02-07-67 | Universal pilot restraint suit and body support therefor |
| *3,302,662 | 02-07-67 | Antiflutter ball check valve |
| 3,302,960 | 02-07-67 | Locking device with rolling detents |
| 3,303,304 | 02-07-67 | Discrete Local Altitude Sensing Device |
| 3,304,028 | 02-14-67 | Attitude control for spacecraft |
| 3,304,718 | 02-21-67 | Double optic system for ion engine |
| 3,304,724 | 02-21-67 | Tank construction for space vehicles |
| 3,304,729 | 02-21-67 | Cryogenic Storage System |
| *3,304,768 | 02-21-67 | Fatigue testing device |
| 3,304,773 | 02-21-67 | Force transducer |
| 3,304,799 | 02-21-67 | Proportional controller |
| 3,304,865 | 02-21-67 | Self-sealing, unbonded, rocket motor nozzle closure |

| Patent No. | Date | Title |
|-------------|----------|--|
| 3,305,415 | 02-21-67 | Process for preparing sterile solid propellants |
| 3,305,636 | 02-21-67 | Phase-shift data transmission system having a pseudo-noise sync code modulated with the data in a single channel |
| **3,305,801 | 02-21-67 | Variable time constant smoothing circuit |
| **3,305,810 | 02-21-67 | Solenoid construction |
| 3,305,861 | 02-21-67 | Closed Loop Ranging System |
| 3,305,870 | 02-21-67 | Dual Mode Horn Antenna |
| 3,307,407 | 03-07-67 | Micro-particle impact sensing apparatus |
| 3,308,848 | 03-14-67 | Fluid power transmission |
| 3,309,012 | 03-14-67 | Thermal pump-compressor for space use |
| 3,309,961 | 03-21-67 | Hermetically sealed explosive release mechanism |
| *3,310,034 | 03-21-67 | File card marker |
| *3,310,138 | 03-21-67 | Viscous-pendulum damper |
| 3,310,256 | 03-21-67 | Aerodynamic protection for space flight vehicles |
| 3,310,258 | 03-21-67 | Technique for control of free-flight rocket vehicles |
| 3,310,261 | 03-21-67 | Control for flexible parawing |
| 3,310,262 | 03-21-67 | Supersonic Aircraft |
| 3,310,443 | 03-21-67 | Method of forming thin window drifted silicon charged particle detector |
| 3,310,978 | 03-28-67 | Fiber optic vibration transducer and analyzer |
| 3,310,980 | 03-28-67 | Hydraulic support for dynamic testing |
| **3,311,315 | 03-28-67 | Endless tape transport mechanism |
| 3,311,502 | 03-28-67 | Didymium hydrate additive to nickel hydroxide electrodes |
| 3,311,510 | 03-28-67 | Method of making a silicon semiconductor device |
| 3,311,748 | 03-28-67 | Sun tracker with rotatable plane-parallel plate and two photocells |
| **3,311,772 | 03-28-67 | Focussing system for an ion source having apertured electrodes |
| 3,311,832 | 03-28-67 | Multiple Input Radio Receiver |
| 3,312,101 | 04-04-67 | Gas Analyzer for Bi-gaseous mixtures |
| 3,316,716 | 05-02-67 | Composite Powerplant and Shroud Therefor |
| 3,316,752 | 05-02-67 | Method and Apparatus for detection and location of microleaks |
| *3,316,991 | 05-02-67 | Automatic Force measuring system |
| 3,317,180 | 05-02-67 | High Pressure regulator valve |
| 3,317,341 | 05-02-67 | Metallic film diffusion for boundary lubrication |
| 3,317,352 | 05-02-67 | Method for determining the state of charge of batteries by the use of tracers |
| 3,317,641 | 05-02-67 | Method For Molding Compounds |
| 3,317,731 | 05-02-67 | Canopus Detector Including Automatic Gain Control of Photomultiplier Tube |
| 3,317,751 | 05-02-67 | Reversible Ring Counter Employing Cascaded Single SCR Stages |
| 3,317,797 | 05-02-67 | Microelectronic Module Package |
| 3,317,825 | 05-02-67 | Three-Wire Ground Type Electrical Receptacle Tester |
| 3,317,832 | 05-02-67 | Single or Joint Amplitude Distribution Analyzer |
| 3,317,846 | 05-02-67 | Linear Accelerator for Micrometeoroids Having a Variable Voltage Source |
| 3,318,093 | 05-09-67 | Hydraulic Drive Mechanism |
| 3,318,096 | 05-09-67 | Purge Device for Thrust Engines |
| 3,318,343 | 05-09-67 | Tool Attachment for Spreading Loose Elements Away From Work |
| *3,318,622 | 05-09-67 | All-Directional Fastener |
| 3,319,175 | 05-09-67 | Electronic Amplifier With Power Supply Switching |
| 3,319,979 | 05-16-67 | Quick Attach and Release Fluid Coupling Assembly |
| 3,320,669 | 05-23-67 | Line Cutter |
| 3,321,034 | 05-23-67 | Sample Collecting Impact Bit |

| Patent No. | Date | Title |
|-------------|----------|---|
| 3,321,154 | 05-23-67 | Transpirationally Cooled Heat Ablation System |
| 3,321,157 | 05-23-67 | Double-Hinged Flap |
| 3,321,159 | 05-23-67 | Techniques for Insulating Cryogenic Fuel Containers |
| *3,321,570 | 05-23-67 | Printed circuit board with bellows rivet connection |
| 3,321,628 | 05-23-67 | Baseline stabilization system for ionization detector |
| **3,321,645 | 05-23-67 | Switching circuit employing regeneratively connected complementary transistors |
| 3,321,922 | 05-30-67 | Small Rocket Engine |
| 3,323,356 | 06-06-67 | Apparatus for Positioning and Loading a test specimen |
| 3,323,362 | 06-06-67 | Positive Displacement Flowmeter |
| 3,323,370 | 06-06-67 | Mass measuring system |
| **3,323,386 | 06-06-67 | Two-axis controller |
| 3,323,408 | 06-06-67 | Optical alignment system |
| 3,323,484 | 06-06-67 | Liquid Flow Sight Assembly |
| **3,323,967 | 06-06-67 | Masking Device |
| 3,324,370 | 06-06-67 | Electronic Beam Switching Commutator |
| 3,324,388 | 06-06-67 | Meteoroid sensing apparatus having a coincidence network connected to a pair of capacitors |
| **3,324,423 | 06-06-67 | Dual waveguide mode source having control means for adjusting the relative amplitudes of two modes |
| 3,324,659 | 06-13-67 | Electrostatic Thruster with Improved Insulators |
| 3,325,229 | 06-13-67 | Air Bearing |
| 3,325,723 | 06-13-67 | Voltage-current characteristic simulator |
| 3,325,749 | 06-13-67 | Variable Frequency Oscillator with Temperature Compensation |
| 3,326,043 | 06-20-67 | Inductive Liquid Level Detection System |
| 3,326,407 | 06-21-67 | Thin-walled pressure vessel |
| 3,327,298 | 06-21-67 | System for recording and reproducing pulse code modulated data |
| *3,327,991 | 06-27-67 | Valve seat with Resilient Support Member |
| 3,328,624 | 06-27-67 | High efficiency ionizer assembly |
| 3,329,375 | 07-04-67 | Attitude Control and damping system for spacecraft |
| 3,329,918 | 07-04-67 | High voltage divider system |
| 3,330,052 | 07-11-67 | Subgravity Simulator |
| **3,330,082 | 07-11-67 | Central spar and module joint |
| 3,330,510 | 07-11-67 | Orbital Escape Device |
| 3,330,549 | 07-11-67 | Shock Absorber |
| 3,331,071 | 07-11-67 | Satellite Communication System |
| 3,331,246 | 07-18-67 | Hypersonic test facility |
| 3,331,255 | 07-18-67 | Non-magnetic, explosive actuated indexing device |
| 3,331,404 | 07-18-67 | Apparatus for purging systems handling |
| 3,331,951 | 07-18-67 | Trigonometric Vehicle Guidance Assembly which aligns the three perpendicular axes of two-axis systems |
| **3,333,152 | 07-25-67 | Self-repeating plasma accelerator |
| 3,333,788 | 08-01-67 | Artificial gravity spin deployment system |
| 3,336,725 | 08-22-67 | Canister closing device |
| 3,336,748 | 08-22-67 | Plasma Device Feed System |
| 3,337,004 | 08-22-67 | Impact energy absorber |
| 3,337,279 | 08-22-67 | Gas purged dry box glove |
| 3,337,315 | 08-22-67 | Method for Fiberizing Ceramic Materials |
| 3,337,337 | 08-22-67 | Method for producing fiber reinforced metallic composites |
| **3,337,790 | 08-22-67 | Mercury capillary interrupter |
| 3,337,812 | 08-22-67 | Circulator having quarter wavelength resonant port and parametric amplifier circuits utilizing the same |
| 3,339,404 | 09-05-67 | Lunar Penetrometer |
| 3,339,863 | 09-05-67 | Solar vane actuator |
| 3,340,099 | 09-05-67 | Bonded elastomeric seal for electrochemical cells |

| Patent No. | Date | Title |
|-------------|----------|--|
| 3,340,395 | 09-05-67 | Time-of-flight mass spectrometer with feed-back means from the detector to the ion sources and a specific counter |
| 3,340,397 | 09-05-67 | Multiple environment materials test chamber having a multiple port X-ray tube for irradiating a plurality of samples |
| **3,340,430 | 09-05-67 | Diode and protection fuse unit |
| 3,340,532 | 09-05-67 | Tracking receiver |
| 3,340,599 | 09-12-67 | Simple method of making photovoltaic junctions |
| 3,340,713 | 09-12-67 | Spin forming tubular elbows |
| 3,340,727 | 09-12-67 | Ablation Probe |
| 3,340,732 | 09-12-67 | Meteorological Balloon |
| 3,341,151 | 09-12-67 | Apparatus providing a directive field pattern and attitude sensing of a spin stabilized satellite |
| 3,341,169 | 09-12-67 | Filler Valve |
| 3,341,708 | 09-12-67 | Amplitude modulated laser transmitter |
| 3,341,778 | 09-12-67 | Optimum pre-detection diversity receiving system |
| **3,341,977 | 09-19-67 | Conforming Polisher for aspheric surfaces of revolution |
| 3,342,055 | 09-19-67 | Protective device for machine and metalworking tools |
| 3,342,066 | 09-19-67 | Model launcher for wind tunnels |
| *3,342,653 | 09-19-67 | Method of making inflatable honeycomb |
| *3,343,180 | 09-26-67 | Stretcher |
| 3,343,189 | 09-26-67 | Rescue litter floatation assembly |
| 3,344,340 | 09-26-67 | Regulated power supply |
| 3,344,425 | 09-26-67 | Monopulse Tracking System |
| 3,345,820 | 10-10-67 | Electron Bombardment Ion Engine |
| 3,345,822 | 10-10-67 | Burning rate control of solid propellants |
| 3,345,840 | 10-10-67 | Tube Dimpling Tool |
| *3,345,866 | 10-10-67 | Multilegged Support System |
| 3,346,419 | 10-10-67 | Solar cell mounting |
| 3,346,515 | 10-10-67 | Method of producing alternating ether-siloxane copolymers |
| 3,346,724 | 10-10-67 | Random Function Tracer |
| 3,346,806 | 10-10-67 | Pressure monitoring with a plurality of ionization gauges controlled at a central location |
| 3,346,929 | 10-17-67 | Latching Mechanism |
| 3,347,046 | 10-17-67 | Control of transverse instability in rocket combustors |
| 3,347,057 | 10-17-67 | Rapid cooling method and apparatus |
| 3,347,309 | 10-17-67 | Self Adjusting Multi-Segment, Deployable Natural Circulation Radiator |
| 3,347,465 | 10-17-67 | Prestressed refractor structure |
| 3,347,466 | 10-17-67 | Nacelle Afterbody for jet engines |
| 3,347,531 | 10-17-67 | Stirring apparatus for plural test tubes |
| 3,347,665 | 10-17-67 | Low temperature aluminum alloy |
| 3,348,048 | 10-17-67 | Horizon sensor with a plurality of fixedly-positioned radiation-compensated radiation sensitive detector |
| 3,348,053 | 10-17-67 | Amplifier Clamping Circuit for horizon scanner |
| 3,348,152 | 10-17-67 | Diversity receiving system |
| 3,349,814 | 10-31-67 | Method and apparatus for making a heat insulating and ablative structure |
| 3,350,038 | 10-31-67 | Reaction wheel scanner |
| 3,350,034 | 10-31-67 | Satellite appendage tie-down cord |
| 3,350,648 | 10-31-67 | Signal-to-noise ratio estimated by taking ratio of mean and standard deviation of integrated signal samples |
| **3,350,671 | 10-31-67 | High power-high voltage waterload |
| **3,350,926 | 11-07-67 | Miniature Stress Transducer |
| 3,352,157 | 11-14-67 | Inertia diaphragm pressure transducer |
| *3,352,192 | 11-14-67 | Split nut separation system |
| 3,353,359 | 11-21-67 | Multislot film cooled pyrolytic graphite rocket nozzle |
| 3,354,098 | 11-21-67 | Elastomeric Silazane polymers and process for preparing the same |
| 3,354,320 | 11-21-67 | Light position locating system |

| Patent No. | Date | Title |
|-------------|----------|---|
| 3,354,462 | 11-21-67 | Event Recorder |
| 3,355,861 | 12-05-67 | Mixture Separation Cell |
| 3,355,948 | 12-05-67 | Spherical Tank Gauge |
| 3,356,320 | 12-05-67 | Device for Separating Occupant from an ejection seat |
| *3,356,549 | 12-05-67 | Method and apparatus for bonding a plastics sleeve onto a metallic body |
| 3,356,885 | 12-05-67 | Small plasma probe |
| 3,357,024 | 12-05-67 | Method of recording a gas flow pattern |
| *3,357,093 | 12-12-67 | Soldering with solder flux which leaves corrosion-resistant coating |
| 3,357,237 | 12-12-67 | Ablation Sensor |
| 3,357,862 | 12-12-67 | Combined Electrolysis device and fuel cell and method of operation |
| 3,358,145 | 12-12-67 | Radiation detector readout system |
| *3,358,264 | 12-12-67 | Coaxial Cable Connector |
| 3,359,046 | 12-10-67 | Bismuth-lead coatings for gas bearings used in atmospheric environments and vacuum chambers |
| 3,359,132 | 12-19-67 | Method of coating circuit paths on printed circuit boards with solder |
| 3,359,409 | 12-19-67 | Correlation function apparatus |
| **3,359,435 | 12-19-67 | Holder for crystal resonators |
| 3,359,555 | 12-19-67 | Polarization diversity monopulse tracking receiver |
| *3,359,819 | 12-26-67 | Bidirectional step torque filter with zero backlash characteristic |
| *3,359,855 | 12-26-67 | Optical projector system |
| 3,360,798 | 12-26-67 | Collapseable reflector |
| 3,360,864 | 01-02-68 | Internal flare angle gauge |
| **3,360,972 | 01-02-68 | Magnetomotive metal working device |
| 3,360,980 | 01-02-68 | Vapor pressure measuring system and method |
| 3,360,988 | 01-02-68 | Electric arc apparatus |
| 3,361,045 | 01-02-68 | Fast-opening diaphragm |
| **3,361,067 | 01-02-68 | Piezoelectric pump |
| 3,361,400 | 01-02-68 | Clamping assembly for components inertial |
| *3,361,666 | 01-02-68 | Inorganic solid film lubricants |
| 3,361,985 | 01-02-68 | Signal detection and tracking apparatus |
| 3,364,311 | 01-16-68 | Elimination of frequency shift in a multiplex communication system |
| 3,364,366 | 01-16-68 | Multiple Slope Sweep Generator |
| *3,364,578 | 01-23-68 | Ellipsograph for Pantograph |
| 3,364,631 | 01-23-68 | Inflatable Support Structure |
| 3,364,777 | 01-23-68 | Null Device for Hand Controller |
| 3,364,813 | 01-23-68 | Self-Calibrating displacement transducer |
| 3,365,580 | 01-23-68 | Film reader with transparent capstan and U-shaped light conducting rod |
| 3,365,657 | 01-23-68 | Power Supply |
| 3,365,665 | 01-23-68 | Hall current measuring apparatus having a series resistor for temperature compensation |
| 3,365,897 | 01-30-68 | Cryogenic Thermal Insulation |
| 3,365,930 | 01-30-68 | Thermal shock apparatus |
| 3,365,941 | 01-30-68 | Precision thrust gage |
| 3,366,886 | 01-30-68 | Linear accelerator frequency control system |
| 3,366,894 | 01-30-68 | Variable duration pulse integrator |
| 3,367,114 | 02-06-68 | Construction and Method of Arranging a Plurality of Ion Engines |
| **3,367,121 | 02-06-68 | Refrigeration device |
| 3,367,182 | 02-06-68 | Heat Flux System |
| 3,367,224 | 02-06-68 | Aligning and Positioning Device |
| 3,367,271 | 02-06-68 | Automatic Pump |
| 3,367,308 | 02-06-68 | Exposure system for animals |
| *3,367,445 | 02-06-68 | Fluid Lubricant System |
| 3,368,486 | 02-13-68 | Single Action Separation Mechanism |
| 3,369,222 | 02-13-68 | Data Compressor |
| 3,369,223 | 02-13-68 | Incremental tape recorder and data rate converter |
| 3,369,564 | 02-20-68 | Transfer Valve |

| Patent No. | Date | Title |
|-------------|----------|--|
| 3,370,039 | 02-20-68 | Process for Preparation of High-Molecular-Weight Polyaryloxyallenes |
| 3,372,588 | 03-12-68 | Constant temperature heat sink for calorimeters |
| *3,373,069 | 03-12-68 | Method of Making an Inflatable Panel |
| 3,373,404 | 03-12-68 | Error-Correcting Method and Apparatus |
| 3,373,430 | 03-12-68 | Omnidirectional Microwave Spacecraft Antenna |
| 3,373,431 | 03-12-68 | Low Noise Single Aperture Multimode Monopulse Antenna Feed System |
| 3,373,640 | 03-19-68 | Apparatus for Machining Geometric Cones |
| 3,373,914 | 03-19-68 | Automatic Welding Speed Controller |
| 3,374,339 | 3-19-68 | Counter and Shift-Register |
| 3,374,366 | 03-19-68 | Complementary Regenerative Switch |
| **3,374,830 | 02-26-68 | Thermal Control Panel |
| 3,374,966 | 03-26-68 | Control System |
| 3,375,451 | 03-26-68 | Adaptive Tracking Notch Filter System |
| 3,375,479 | 03-26-68 | Continuous Turning Slip Ring Assembly |
| 3,376,730 | 04-09-68 | Friction Measuring Apparatus |
| 3,377,208 | 04-09-68 | Thermocouple Assembly |
| 3,377,845 | 04-16-68 | Moment of Inertia Test Fixture |
| 3,378,315 | 04-16-68 | Hybrid Lubrication System and Bearing |
| 3,378,851 | 04-23-68 | Soft Frame Adjustable Eyeglasses |
| *3,378,892 | 04-23-68 | Quick Attach Mechanism |
| 3,379,064 | 04-23-68 | Automatic Recording McLeod Gauge |
| 3,379,330 | 04-23-68 | Cryogenic Insulation System |
| 3,379,885 | 04-23-68 | Sight Switch Using an Infrared Source and Sensor |
| 3,379,974 | 04-23-68 | Particle Detection Apparatus Including a Ballistic Pendulum |
| 3,380,042 | 04-23-68 | Digital Telemetry System |
| 3,380,049 | 04-23-68 | Method of Resolving Clock Synchronization Error and Means Therefor |
| *3,381,339 | 05-07-68 | Hydraulic Casting of Liquid Polymers |
| 3,381,517 | 05-07-68 | Rotary Bead Dropper and Selector For Testing Micrometeorite Detectors |
| 3,381,527 | 05-07-68 | Tension Measurement Device |
| 3,381,569 | 05-17-68 | Attitude Sensor For Space Vehicles |
| 3,381,778 | 05-07-68 | Energy Absorbing Device |
| *3,382,082 | 05-07-68 | Foamed-In-Place Ceramic Refractory Insulating Material |
| 3,382,105 | 05-17-68 | Ion-Exchange Membrane and Electrode Assembly |
| 3,382,107 | 05-17-68 | Sealing Device For An Electrochemical Cell |
| 3,382,714 | 05-14-68 | Heat Sensing Instrument |
| 3,383,461 | 05-14-68 | Reduced Bandwidth Video Communication System Utilizing Sampling Technique |
| 3,383,524 | 05-14-68 | Solid State Pulse Generator With Constant Output Width, For Variable Input Width, In Nanosecond Range |
| 3,383,903 | 05-21-68 | Pressure Transducer Calibrator |
| 3,383,922 | 05-21-68 | Linear Differential Pressure Sensor |
| 3,384,016 | 05-21-68 | Lateral Displacement System For Separated Rocket Stages |
| 3,384,075 | 05-21-68 | Thermal Control Wall Panel |
| 3,384,111 | 05-21-68 | Positive Locking Check Valve |
| **3,384,324 | 05-21-68 | Thermal Control Wall Panel |
| *3,384,820 | 05-21-68 | Vibrating Element Electrometer With Output Signal Magnified Over Input Signal By A Function Of The Mechanical Q Of The Vibrating Element |
| 3,384,895 | 05-21-68 | Portable Superclean Air Column Device |
| 3,385,036 | 05-28-68 | Portable Superclean Air Column Device |
| 3,386,337 | 06-04-68 | Portable Milling Tool |
| **3,386,685 | 06-04-68 | Spacecraft Airlock |
| 3,386,686 | 06-04-68 | Station Keeping Of A Gravity-Gradient Stabilized Satellite |
| 3,387,149 | 06-04-68 | Phonocardiograph Transducer |
| 3,388,258 | 06-11-68 | Fluid Flow Meter With Comparator Reference Means |

| Patent No. | Date | Title |
|-------------|----------|---|
| **3,388,387 | 06-11-68 | Drive Circuit Utilizing Two Cores |
| **3,388,590 | 06-18-68 | Connector Internal Force Gauge |
| 3,389,017 | 06-18-68 | Sealing Member And Combination Thereof And Method Of Producing Said Sealing Member |
| 3,389,260 | 06-18-68 | Solar Sensor Having Coarse And Fine Sensing With Matched Preirradiated Cells And Method Of Selecting Cells |
| 3,389,346 | 06-18-68 | Compensating Bandwidth Switching Transients In An Amplifier Circuit |
| 3,389,877 | 06-25-68 | Inflatable Tether |
| 3,390,017 | 06-25-68 | Sealed Electrochemical Cell Provided With A Flexible Casing |
| 3,390,020 | 06-25-68 | Semiconductor Material And Method Of Making Same |
| 3,390,282 | 06-25-68 | Passive Synchronized Spike Generator With High Input Impedance And Low Output Impedance And Capacitor Power Supply |
| **3,390,378 | 06-25-68 | Comparator For The Comparison Of Two Binary Numbers |
| 3,391,080 | 07-02-68 | Metallic Film Diffusion For Boundary Lubrication |
| 3,392,403 | 07-09-68 | Measurement Of Time Differences Between Luminous Events |
| 3,392,586 | 07-16-68 | Device For Measuring Pressure |
| 3,392,864 | 07-16-68 | Insulation System |
| 3,392,865 | 07-16-68 | Filament-Wound Container |
| 3,392,936 | 07-16-68 | Leading Edge Curvature Based On Convective Heating |
| **3,393,059 | 07-16-68 | Decontamination Of Petroleum Products |
| 3,393,330 | 07-16-68 | Thermionic Converter With Current Augmented By Self-Induced Magnetic Field |
| 3,393,332 | 07-16-68 | Superconducting Alternator |
| 3,393,380 | 07-16-68 | Phase Locked Phase Modulator Including A Voltage Controlled Oscillator |
| 3,393,347 | 07-16-68 | Power Supply Circuit |
| 3,393,384 | 07-16-68 | Radio Frequency Coaxial High Pass Filter |
| 3,394,359 | 07-23-68 | Digital Memory Sense Amplifying Means |
| 3,394,975 | 07-30-68 | Petzval Type Objective Including Field Shaping Lens |
| **3,395,053 | 07-30-68 | Thermal Control Coating |
| 3,396,057 | 08-06-68 | Method Of Electrolytically Binding A Layer Of Semiconductors Together |
| 3,396,184 | 08-06-68 | Trialkyl-Dihalotantalum And Niobium Compounds |
| 3,396,303 | 08-06-68 | ARC Electrode Of Graphite With Ball Tip |
| 3,396,584 | 08-13-68 | Space Simulation And Radiative Property Testing System And Method |
| 3,396,920 | 08-13-68 | Apparatus For Changing The Orientation And Velocity Of A Spinning Body Traversing A Path |
| **3,397,094 | 08-13-68 | Method Of Changing The Conductivity Of Vapor Deposited Gallium Arsenide By The Introduction Of Water Into The Vapor Deposition Atmosphere |
| *3,397,117 | 08-13-68 | Compact Solar Still |
| 3,397,318 | 08-13-68 | Ablation Sensor |
| 3,397,512 | 08-20-68 | Vapor-Liquid Separator |
| 3,397,932 | 08-20-68 | Semi-Linear Ball Bearing |
| 3,399,299 | 08-27-68 | Apparatus For Phase Stability Determination |
| 3,399,574 | 09-03-68 | Method For Leakage Testing Of Tanks |
| 3,404,848 | 10-01-68 | Low Level Signal Limiter |
| 3,405,406 | 10-15-68 | Hard Space Suit |
| 3,405,887 | 10-15-68 | Ring Wing Tension Vehicle |
| 3,406,336 | 10-15-68 | RC Rate Generator For Slow Speed Measurement |
| *3,406,742 | 10-22-68 | Automatic Fatigue Test Temperature Programmer |

| Patent No. | Date | Title |
|------------|----------|---|
| 3,407,304 | 10-22-68 | Micrometeoroid Penetration Measuring Device |
| 3,408,816 | 11-05-68 | Rocket Engine Injector |
| 3,408,861 | 11-05-68 | Rocket Engine Thrust Vector Deviation Measurement Device |
| 3,408,870 | 11-05-68 | Zero Gravity Apparatus |
| 3,409,247 | 11-05-68 | Solid State Thermal Control Polymer Coating |
| 3,409,252 | 11-05-68 | Controllers |
| 3,409,554 | 11-05-68 | Gd or Sm Doped Silicon Semi-Conductor Composition |
| 3,409,730 | 11-05-68 | Thermal Radiation Shielding |
| *3,411,356 | 11-19-68 | Zeta Potential Flow Meter |
| 3,412,559 | 11-26-68 | Ion Engine Casing Construction And Method Of Making Same |
| 3,412,598 | 11-26-68 | Impact Testing Machine |
| *3,412,729 | 11-26-68 | Method And Apparatus For Continuously Monitoring Blood Oxygenation, Blood Pressure, Pulse Rate And The Pressure Pulse Curve Utilizing An Ear Oximeter As Transducer |
| 3,412,961 | 11-26-68 | Means For Suppressing Or Attenuating Bending Motion Of Elastic Bodies |
| *3,413,115 | 11-26-68 | Brazing Alloy |
| 3,413,510 | 11-26-68 | Electronic Cathode Having A Brush-Like Structure And A Relatively Thick Oxide Emissive Coating |
| 3,413,536 | 11-26-68 | Automatic Battery Charger |
| 3,414,012 | 12-03-68 | Dual Latching Solenoid Valve |
| 3,414,358 | 12-03-68 | Optical Monitor Panel |
| 3,415,032 | 12-10-68 | Evacuation Port Seal |
| 3,415,069 | 12-10-68 | High Pressure Helium Purifier |
| 3,415,116 | 12-10-68 | Floating Two-Force-Component Measuring Device |
| 3,415,126 | 12-10-68 | Azimuth Laying System |
| 3,415,156 | 12-10-68 | Controlled Release Device |
| *3,415,556 | 12-10-68 | Ceramic-To-Metal Seal And Method Of Making Same |
| 3,415,643 | 12-10-68 | High Temperature Ferromagnetic Cobalt-Base |
| 3,415,992 | 12-10-68 | Extended Area Semiconductor Radiation Detectors And A Novel Readout Arrangement |
| 3,416,106 | 12-10-68 | Broadband Microwave Waveguide Window |
| 3,416,274 | 12-17-68 | Flexibly Connected Support And Skin |
| *3,416,939 | 12-17-68 | Alkali-Metal Silicate Protective Coating |
| 3,416,975 | 12-17-68 | Etching Of Aluminum For Bonding |
| 3,416,988 | 12-17-68 | Traveling Sealer For Contoured Table |
| 3,417,247 | 12-17-68 | Radiant Energy Intensity Measurement System |
| 3,417,266 | 12-17-68 | Pulse Modulator Providing Fast Rise And Fall Times |
| 3,417,298 | 12-17-68 | Polarity Sensitive Circuit |
| 3,417,316 | 12-17-68 | Sidereal Frequency Generator |
| 3,417,321 | 12-17-68 | Increasing Efficiency Switching-Type Regulator Circuits |
| 3,417,332 | 12-17-68 | Frequency Shift Keying Apparatus |
| 3,417,399 | 12-17-68 | Millimeter-Wave Radiometer For Radio-Astronomy |
| 3,417,400 | 12-17-68 | Triaxial Antenna |
| *3,419,329 | 12-31-68 | Combined Optical Attitude And Altitude Indicating Instrument |
| 3,419,363 | 12-31-68 | Self-Lubricating Fluoride-Metal Composite Materials |
| 3,419,433 | 12-31-68 | Solar Cell And Circuit Array And Process For Nullifying Magnetic Fields |
| *3,419,537 | 12-31-68 | Dicyanoacetylene Polymers |
| *3,419,827 | 12-31-68 | Indexing Microwave Switch |
| 3,419,964 | 01-07-69 | Apparatus For Measuring Swelling Characteristics Of Membranes |
| 3,420,069 | 01-07-69 | Condenser-Separator |

| Patent No. | Date | Title |
|-------------|----------|---|
| *3,420,223 | 01-07-69 | Electrode For Biological Recording |
| 3,420,225 | 01-07-69 | Balanced Bellows Spirometer |
| 3,420,338 | 01-07-69 | Hermetic Sealed Vibration Damper |
| 3,420,704 | 01-07-69 | Depositing Semiconductor Films Utilizing A Thermal Gradient |
| 3,420,945 | 01-07-69 | Electrode and Insulator With Shielded Dielectric Junction |
| **3,420,978 | 01-07-69 | Pretreatment Method For Anti-Wettable Materials |
| 3,421,004 | 01-07-69 | Solar Optical Telescope Dome Control System |
| 3,421,053 | 01-07-69 | Tumbler System To Provide Random Motion |
| 3,421,056 | 01-07-69 | Thin Window Drifted Silicon, Charged Particle Detector |
| 3,421,105 | 01-07-69 | Automatic Acquisition System For Phase-Lock Loop |
| *3,421,134 | 01-07-69 | Electrical Connector |
| 3,421,363 | 01-14-69 | Harness For Vertically Supporting Slender Bodies For Vibration Testing |
| 3,421,506 | 01-14-69 | Relief Container |
| 3,421,541 | 01-14-69 | Relief Valve |
| 3,421,549 | 01-14-69 | Pneumatic System For Controlling And Actuating Pneumatic Cyclic Devices |
| *3,421,591 | 01-14-69 | Rock Drill For Recovering Samples |
| 3,421,700 | 01-14-69 | Electromechanical Actuator |
| 3,421,768 | 01-14-69 | Foil Seal |
| **3,421,864 | 01-14-69 | Multilayer Porous Ionizer |
| **3,421,948 | 01-14-69 | Method Of Making Membranes |
| 3,422,019 | 01-14-69 | Method For Processing Ferrite Cores |
| 3,422,213 | 01-14-69 | Connector Strips |
| 3,422,278 | 01-14-69 | Signal Generator |
| **3,422,291 | 01-14-69 | Magnetohydrodynamic Induction Machine |
| *3,422,324 | 01-14-69 | Pressure Variable Capacitor |
| 3,422,352 | 01-14-69 | Apparatus For Measuring Current Flow |
| **3,422,354 | 01-14-69 | Test Fixture For Pellet-Like Electrical Elements |
| 3,422,390 | 01-14-69 | Coupling Device |
| 3,422,403 | 01-14-69 | Data Compression System |
| 3,422,440 | 01-14-69 | Plural Recorder System |
| 3,423,179 | 01-21-69 | Catalyst For Growth Of Boron Carbide Crystal Whiskers |
| 3,423,290 | 01-21-69 | Lyophilized Reaction Mixtures |
| *3,423,579 | 01-21-69 | Electronic Divider And Multiplier Using Photoconductor |
| 3,423,608 | 01-21-69 | Nonmagnetic Thermal Motor For A Magnetometer |
| 3,424,966 | 01-28-69 | Synchronous Servo Loop Control System |
| 3,425,131 | 02-04-69 | Extensometer |
| 3,425,486 | 02-04-69 | Garments For Controlling The Temperature Of The Body |
| 3,425,487 | 02-04-69 | Space Suit Heat Exchanger |
| *3,426,230 | 02-04-69 | Direct Radiation Cooling Of The Collector Of Linear Beam Tubes |
| **3,426,263 | 02-04-69 | Method And Apparatus For Battery Charge Control |
| **3,426,272 | 02-04-69 | Device For Determining The Accuracy Of The Flare On A Flared Tube |
| 3,426,746 | 02-11-69 | Method And Apparatus For Attaching Physiological Monitoring Electrodes |
| 3,427,089 | 02-11-69 | Ultraviolet Filter |
| 3,427,097 | 02-11-69 | Pneumatic Mirror Support System |
| 3,427,205 | 02-11-69 | Spacecraft Battery Seals |
| 3,427,525 | 02-11-69 | Regulated D.C. to D.C. Converter |
| 3,428,761 | 02-18-69 | Excitation And Detection Circuitry For A Flux Responsive Magnetic Head |
| 3,428,812 | 02-18-69 | Optical Spin Compensator |
| 3,428,910 | 02-18-69 | Automatic Gain Control System |
| 3,428,919 | 02-18-69 | Signal Multiplexer |
| 3,428,928 | 02-18-69 | Broadband Choke For Antenna Structure |
| 3,429,477 | 02-25-69 | Apparatus for Ejection Of An Instrument Cover |

| Patent No. | Date | Title |
|------------|----------|---|
| 3,429,529 | 02-25-69 | Control Devices For Flexible Wing Aircraft |
| 3,430,115 | 02-25-69 | Apparatus For Ballasting High Frequency Transistors |
| 3,430,182 | 02-25-69 | Electrical Feed-Through Connection For Printed Circuit Boards And Printed Cables |
| 3,430,237 | 02-25-69 | Time Division Multiplex System |
| 3,430,909 | 03-04-69 | Device For Handling Heavy Loads |
| 3,432,730 | 03-11-69 | Semiconductor P-N Junction Stress And Strain Sensor |
| 3,433,015 | 03-18-69 | Gas Turbine Combustion Apparatus |
| *3,433,953 | 03-18-69 | Compensating Radiometer |
| 3,433,960 | 03-18-69 | Retrodirective Optical System |
| 3,433,961 | 03-18-69 | Scanning Aspect Sensor Employing An Apertured Disc And A Commutator |
| 3,434,037 | 03-18-69 | Multiple Varactor Frequency Doubler |
| 3,434,050 | 03-18-69 | High Impedance Measuring Apparatus |
| 3,434,064 | 03-18-69 | Amplifier Drift Tester |
| 3,434,885 | 03-25-69 | Method Of Making Electrical Contact On Silicon Solar Cell And Resulant Product |
| 3,435,246 | 03-25-69 | Light Radiation Direction Indicator With A Baffle Of Two Parallel Grids |
| 3,437,527 | 04-08-69 | Method For Producing A Solar Cell Having An Integral Protective Covering |
| 3,437,560 | 04-08-69 | Use Of The Enzyme Hexokinase For The Reduction Of Inherent Light Levels |
| 3,437,832 | 04-08-69 | Ring Counter |
| 3,437,874 | 04-08-69 | Display For Binary Characters |
| 3,437,903 | 04-08-69 | Protection For Energy Conversion Systems |
| 3,437,919 | 04-08-69 | Cryogenic Apparatus For Measuring The Intensity Of Magnetic Fields |
| 3,437,935 | 04-08-69 | Varactor High Level Mixer |
| 3,437,959 | 04-08-69 | Helical Coaxial Resonator RF Filter |
| 3,438,044 | 04-08-69 | Monopulse System With An Electronic Scanner |
| 3,438,263 | 04-15-69 | Fluid Sample Collector |
| 3,439,886 | 04-22-69 | Visual Target For Retrofire Attitude Control |
| 3,443,208 | 05-06-69 | Optically Pumped Resonance Magnetometer For Determining Vectorial Components In A Spatial Coordinate System |
| 3,444,380 | 05-13-69 | Electronic Background Suppression Method And Apparatus For A Field Scanning Sensor |
| 3,446,387 | 05-27-69 | Piping Arrangement Through A Double Wall Chamber |
| 3,446,676 | 05-27-69 | Solar Battery With Interconnecting Means For Plural Cells |
| 3,446,960 | 05-27-69 | Device For Measuring Electron-Beam Intensities And For Subjecting Materials To Electron Irradiation In An Electron Microscope |
| 3,446,992 | 05-27-69 | Bus Voltage Compensation Circuit For Controlling Direct Current Motor |
| 3,446,998 | 05-27-69 | Bi-metallic Power Controlled Actuator |
| 3,447,015 | 05-27-69 | Ion Thruster Cathode |
| 3,447,071 | 05-27-69 | Probes Having Guard Ring and Primary Sensor At Same Potential To Prevent Collection Of Stray Wall Currents In Ionized Gases |
| 3,447,154 | 05-27-69 | Cooperative Doppler Radar System |
| 3,447,155 | 05-27-69 | Ranging System |
| 3,447,283 | 06-03-69 | Bonding Thermoelectric Elements To Nonmagnetic Refractory Metal Electrodes |
| 3,477,774 | 06-03-69 | High Pressure Air Valve |
| 3,448,346 | 06-03-69 | Extensible Cable Support |
| 3,448,273 | 06-03-69 | Plurality of Photosensitive Cells On A Pyramidal Base For Planetary Trackers |
| 3,448,290 | 06-03-69 | Variable-Width Pulse Integrator |
| 3,448,341 | 06-03-69 | Electrical Load Protection Device |

| Patent No. | Date | Title | Patent No. | Date | Title |
|-------------|----------|---|------------|----------|--|
| 3,447,850 | 06-03-69 | Sealed Cabinetry | 3,460,378 | 08-12-69 | Strain Gauge Measuring Techniques |
| 3,450,878 | 06-17-69 | Dosimeter For High Levels of Absorbed Radiation | 3,460,759 | 08-12-69 | Combustion Chamber |
| 3,450,842 | 06-17-69 | Doppler Frequency Spread Correction Device For Multiplex Transmissions | 3,460,379 | 08-12-69 | Tensile Strength Testing Device |
| 3,450,946 | 06-17-69 | Protective Circuit of the Spark Gap Type | 3,461,437 | 08-12-69 | Digital Memory In Which the Driving Of Each Word Location Is Controlled By A Switch Core |
| 3,452,976 | 07-01-69 | Printed Circuit Soldering Aid | 3,460,397 | 08-12-69 | Mechanical Actuator |
| 3,452,872 | 07-01-69 | Shock-Layer Radiation Measurement | 3,461,393 | 08-12-69 | Cascaded Complementary Pair Broad-band Transistor Amplifiers |
| 3,453,172 | 07-01-69 | Bonding Graphite With Fused Silver Chloride | 3,461,290 | 08-12-69 | Conically Shaped Cavity Radiometer With a Dual Purpose Cone Winding |
| 3,452,423 | 07-01-69 | Segmenting Lead Telluride-Silicon Germanium Thermoelements | 3,461,721 | 08-19-69 | Flow Field Simulation |
| 3,458,313 | 07-29-69 | High Resolution Developing of Photo-sensitive Resists | 3,461,855 | 08-19-69 | Conditioning Suit |
| 3,458,833 | 07-29-69 | Frequency Control Network For a Current Feedback Oscillator | 3,463,563 | 08-26-69 | Swivel Support For Gas Bearings |
| 3,458,104 | 07-29-69 | Weld Control System Using Thermocouple Wire | 3,464,049 | 08-26-69 | Load Cell Protection Device |
| 3,458,162 | 07-29-69 | Control Devices for Flexible Wing Aircraft | 3,463,939 | 08-26-69 | Pulsed Differential Comparator Circuit |
| 3,458,112 | 07-15-69 | Temperature Sensitive Capacitor Device | 3,464,051 | 08-26-69 | Electrical Spot Terminal Assembly |
| 3,456,193 | 07-15-69 | Phase Quadrature-Plural Channel Data Transmission System | 3,464,012 | 08-26-69 | Automatic Signal Range Selector For Metering Devices |
| 3,458,702 | 07-29-69 | Telespectrograph | 3,463,001 | 08-26-69 | Thrust Dynamometer |
| 3,458,651 | 07-29-69 | Television Simulation For Aircraft and Space Flight | 3,464,016 | 08-26-69 | Demodulation System |
| 3,458,726 | 07-29-69 | Power Control Circuit | 3,463,673 | 08-26-69 | Electrochemical Coulometer and Method of Forming |
| 3,453,462 | 07-01-69 | Slug Flow Magnetohydrodynamic Generator | 3,464,018 | 08-26-69 | Digitally Controlled Frequency Synthesizer |
| 3,453,546 | 07-01-69 | Telemeter Adaptable for Implanting In An Animal | 3,464,652 | 09-02-69 | Control Devices For Flexible Wing Aircraft |
| **3,454,410 | 07-08-69 | Alkali-Metal Silicate Protective Coating | 3,466,243 | 09-09-69 | Alloys for Bearings |
| 3,455,171 | 07-15-69 | Inertial Reference Apparatus | 3,465,482 | 09-09-69 | Spacecraft Radiator Cover |
| 3,456,201 | 07-15-69 | System For Monitoring Signal Amplitude Ranges | 3,466,198 | 09-09-69 | Solar Cell Matrix |
| 3,458,851 | 07-29-69 | Electrical Connector Pin With Wiping Action | 3,466,085 | 09-09-69 | Articulated Multiple Couch Assembly |
| 3,458,217 | 07-29-69 | Tubular Coupling Having Low Profile Band Segments With Means for Preventing Relative Rotation | 3,466,459 | 09-09-69 | Current Steering Switch |
| 3,455,121 | 07-15-69 | Water Separating System | 3,466,570 | 09-09-69 | Inverter With Means For Base Current Shaping For Sweeping Charge Carriers From Base Region |
| *3,459,391 | 08-05-69 | Interconnection of Solar Cells | 3,465,986 | 09-09-69 | Satellite Despin Device |
| 3,460,995 | 08-12-69 | Method and Device for Determining Battery State of Charge | 3,466,484 | 09-09-69 | Ionization-Vacuum Gauge With All But The End of the Ion-collector Shielded |
| 3,460,381 | 08-12-69 | Balance Torquemeter | 3,466,424 | 09-09-69 | Evaporant Source for Vapor Deposition |
| 3,460,781 | 08-12-69 | Tape Recorder | 3,466,052 | 09-09-69 | Foil Seal |
| 3,460,784 | 08-12-69 | Control Devices for Flexible Wing Aircraft | 3,465,567 | 09-09-69 | Method of Making Tubes |
| | | | 3,465,569 | 09-09-69 | Low Temperature Flexure Fatigue Cryostat |
| | | | 3,465,747 | 09-09-69 | Ballistocardiograph |
| | | | 3,466,418 | 09-09-69 | Determination of Spot Weld Quality |
| | | | 3,466,560 | 09-09-69 | Stable Amplifier Having A Stable Quiescent Point |